



Anlin Del Mar

Style	Glazing Option	Air Argon	U-Factor	SHGC No-Grid	SHGC Grid	VLT	UV Block	Air Infiltration	CRF	STC Ratings		
										Standard 1/8 over 1/8	Sound Pack 3/16 over 1/8	Laminated 7/32 over 1/8
Single Slider	SunMatrix Plus	Air	.30	.18	.17	52%	99%	0.04	59	29	34	35
Single Hung	SunMatrix Plus	Air	.30	.18	.17	52%	99%	0.03	55	28	35	37
Picture Window	SunMatrix Plus	Air	.29	.20	.18	52%	99%	<.01	57	29	34	35
Single Slider	SunMatrix Plus	Argon	.26	.17	.16	52%	99%	0.04	63	29	34	35
Single Hung	SunMatrix Plus	Argon	.26	.17	.16	52%	99%	0.03	58	28	35	37
Picture Window	SunMatrix Plus	Argon	.25	.19	.18	52%	99%	<.01	61	29	34	35
Single Slider	SunMatrix Plus/QT	Air	.25	.18	.16	50%	99%	0.04	46	29	34	35
Single Hung	SunMatrix Plus/QT	Air	.25	.18	.16	50%	99%	0.03	43	28	35	37
Picture Window	SunMatrix Plus/QT	Air	.24	.19	.17	50%	99%	<.01	44	29	34	35
Single Slider	SunMatrix Plus/QT	Argon	.22	.17	.16	50%	99%	0.04	50	29	34	35
Single Hung	SunMatrix Plus/QT	Argon	.22	.17	.16	50%	99%	0.03	47	28	35	37
Picture Window	SunMatrix Plus/QT	Argon	.21	.19	.17	50%	99%	<.01	48	29	34	35
Single Slider	Infinite Plus	Air	.30	.22	.20	65%	95%	0.04	59	29	34	35
Single Hung	Infinite Plus	Air	.30	.22	.20	65%	95%	0.03	55	28	35	37
Picture Window	Infinite Plus	Air	.29	.24	.22	65%	95%	<.01	57	29	34	35
Single Slider	Infinite Plus	Argon	.26	.22	.20	65%	95%	0.04	63	29	34	35
Single Hung	Infinite Plus	Argon	.26	.22	.20	65%	95%	0.03	56	28	35	37
Picture Window	Infinite Plus	Argon	.25	.24	.22	65%	95%	<.01	61	29	34	35
Single Slider	Infinite Plus/QT	Air	.26	.22	.20	63%	95%	0.04	46	29	34	35
Single Hung	Infinite Plus/QT	Air	.25	.22	.20	63%	95%	0.03	43	28	35	37
Picture Window	Infinite Plus/QT	Air	.24	.24	.21	63%	95%	<.01	44	29	34	35
Single Slider	Infinite Plus/QT	Argon	.22	.22	.20	63%	95%	0.04	50	29	34	35
Single Hung	Infinite Plus/QT	Argon	.22	.22	.20	63%	95%	0.03	48	28	35	37
Picture Window	Infinite Plus/QT	Argon	.21	.23	.21	63%	95%	<.01	48	29	34	35

Plus - Easy Clean Exterior Coating **QT** - Heat Retention Coating **SHGC** - Solar Heat Gain Coefficient **CRF** - Condensation Resistance Factor **STC** - Sound Transmission Class

VLT - Visible Light Transmittance (Note: VLT on NFRC label will vary as calculation is based on complete unit, not viewing area)



Anlin Del Mar

Style	Glazing Option	Air Argon	U-Factor	SHGC No-Grid	SHGC Grid	VLT	UV Block	Air Infiltration	CRF	STC Ratings		
										Standard 1/8 over 1/8	Sound Pack 3/16 over 1/8	Laminated 7/32 over 1/8
Single Slider	SunShield Plus	Air	.30	.15	.14	39%	98%	0.04	59	29	34	35
Single Hung	SunShield Plus	Air	.30	.15	.14	39%	98%	0.03	54	28	35	37
Picture Window	SunShield Plus	Air	.30	.16	.15	39%	98%	<.01	57	29	34	35
Single Slider	SunShield Plus	Argon	.27	.15	.13	39%	98%	0.04	63	29	34	35
Single Hung	SunShield Plus	Argon	.27	.15	.13	39%	98%	0.03	58	28	35	37
Picture Window	SunShield Plus	Argon	.26	.16	.14	39%	98%	<.01	61	29	34	35
Single Slider	SunShield Plus/QT	Air	.26	.14	.13	38%	98%	0.04	46	29	34	35
Single Hung	SunShield Plus/QT	Air	.25	.14	.13	38%	98%	0.03	43	28	35	37
Picture Window	SunShield Plus/QT	Air	.24	.16	.14	38%	98%	<.01	44	29	34	35
Single Slider	SunShield Plus/QT	Argon	.23	.14	.13	38%	98%	0.04	50	29	34	35
Single Hung	SunShield Plus/QT	Argon	.23	.14	.13	38%	98%	0.03	47	28	35	37
Picture Window	SunShield Plus/QT	Argon	.21	.15	.14	38%	98%	<.01	48	29	34	35
Single Slider	CoolShield Plus	Air	.31	.30	.27	70%	86%	0.04	59	29	34	35
Single Hung	CoolShield Plus	Air	.31	.30	.27	70%	86%	0.03	54	28	35	37
Picture Window	CoolShield Plus	Air	.30	.32	.29	70%	86%	<.01	57	29	34	35
Single Slider	CoolShield Plus	Argon	.27	.30	.27	70%	86%	0.04	63	29	34	35
Single Hung	CoolShield Plus	Argon	.27	.30	.27	70%	86%	0.03	58	28	35	37
Picture Window	CoolShield Plus	Argon	.26	.32	.29	70%	86%	<.01	61	29	34	35
Single Slider	CoolShield Plus/QT	Air	.26	.29	.26	69%	86%	0.04	45	29	34	35
Single Hung	CoolShield Plus/QT	Air	.26	.29	.26	69%	86%	0.03	43	28	35	37
Picture Window	CoolShield Plus/QT	Air	.24	.31	.29	69%	86%	<.01	44	29	34	35
Single Slider	CoolShield Plus/QT	Argon	.23	.29	.26	69%	86%	0.04	50	29	34	35
Single Hung	CoolShield Plus/QT	Argon	.23	.29	.26	69%	86%	0.03	46	28	35	37
Picture Window	CoolShield Plus/QT	Argon	.21	.31	.28	69%	86%	<.01	48	29	34	35

Plus - Easy Clean Exterior Coating **QT** - Heat Retention Coating **SHGC** - Solar Heat Gain Coefficient **CRF** - Condensation Resistance Factor **STC** - Sound Transmission Class

VLT - Visible Light Transmittance (Note: VLT on NFRC label will vary as calculation is based on complete unit, not viewing area)



Anlin Del Mar

Style	Glazing Option	Air Argon	U-Factor	SHGC No-Grid	SHGC Grid	VLT	UV Block	Air Infiltration	CRF	STC Ratings		
										Standard 1/8 over 1/8	Sound Pack 3/16 over 1/8	Laminated 7/32 over 1/8
Single Slider	Luminance	Air	.32	.52	.46	79%	71%	0.04	58	29	34	35
Single Hung	Luminance	Air	.32	.52	.46	79%	71%	0.03	54	28	35	37
Picture Window	Luminance	Air	.31	.56	.50	79%	71%	<.01	56	29	34	35
Single Slider	Luminance	Argon	.28	.51	.46	79%	71%	0.04	62	29	34	35
Single Hung	Luminance	Argon	.28	.51	.46	79%	71%	0.03	57	28	35	37
Picture Window	Luminance	Argon	.27	.56	.50	79%	71%	<.01	60	29	34	35
Single Slider	Luminance/QT	Air	.26	.49	.44	77%	73%	0.04	45	29	34	35
Single Hung	Luminance/QT	Air	.26	.49	.44	77%	73%	0.03	42	28	35	37
Picture Window	Luminance/QT	Air	.25	.54	.48	77%	73%	<.01	43	29	34	35
Single Slider	Luminance/QT	Argon	.24	.50	.45	77%	73%	0.04	49	29	34	35
Single Hung	Luminance/QT	Argon	.24	.50	.45	77%	73%	0.03	46	28	35	37
Picture Window	Luminance/QT	Argon	.22	.54	.49	77%	73%	<.01	47	29	34	35

Plus - Easy Clean Exterior Coating **QT** - Heat Retention Coating **SHGC** - Solar Heat Gain Coefficient **CRF** - Condensation Resistance Factor **STC** - Sound Transmission Class
VLT - Visible Light Transmittance (Note: VLT on NFRC label will vary as calculation is based on complete unit, not viewing area)



Anlin Del Mar

Structural Performance Data

Del Mar	Min Size	Max Size	Rating ⁽¹⁾
Single Hung (SH)	12 1/4 x 21	48 x 120 ⁽³⁾	LC30
Single Slider (XO,OX)	21 x 12 1/2	72 x 60	LC30
	21 x 13 ⁽²⁾	96 x 72	R20
End Vent Slider (XOX)	42 x 12 1/2	144 x 72 ⁽⁵⁾	R20
	42 x 13 ⁽²⁾		
Picture Window (PW)	8 1/2 x 8 1/2	96 x 72	HC45
		120 x 60 ⁽⁴⁾	HC50

Del Mar - Maximum View/Egress	Min Size	Max Size	Rating ⁽¹⁾
Single Hung (SH)	10 3/4 x 21	48 x 120 ⁽³⁾	LC30
Single Slider (XO,OX)	21 x 9	96 x 72	R20
	21 x 13 ⁽²⁾		
End Vent Slider (XOX)	42 x 9	144 x 72 ⁽⁵⁾	R20
	42 x 13 ⁽²⁾		

- (1) Rating based on Max Size unit
- (2) Minimum Size with True Action Lock and Sash Bolt Option
- (3) Maximum Single Hung vent height is 36"
- (4) PW over 96" wide must be tempered
- (5) End Vent Slider (XOX) configuration is 4/2/4

Combinations ⁽¹⁾	Min Size	Max Size	Rating
SH/SH or PW/SH or SH/PW	26 1/2 x 22 1/2	96 x 96	R20
SH/SH/SH or SH/PW/SH	39 3/4 x 22 1/2	144 x 84	R25
PW over XO, OX	21 x 24	96 x 96	R20
PW over XOX	42 x 24	96 x 96	R20
PW/PW	18 x 8 1/2	120 x 96	R15
PW/PW/PW	27 x 8 1/2	144 x 72	R15

(1) Del Mar Max View not available in one frame Combinations.